



TVW2255 Video Wall Trolley 2x2

Key Benefits

- Quick to install
- Easy to align on X-Y-Z axis
- Solution for every configuration
- Attractive design
- TÜV-5 certified

Would you like to place your 2x2 video wall in a freestanding environment? And does it also need to be mobile? Vogel's has put together a complete kit for a professional mobile video wall solution. A video wall trolley. This video wall trolley kit is suitable for 55 inch LCD displays with a maximum weight of 80 kg/display. This modular system is quick and easy to install. Combine the video wall trolley undercarriage and crossbar with the PUC 29 poles, display interface bars and display interface strips to create your perfect video wall. With the specially designed (3D) interface strips, you can easily align any screen on the X, Y and Z axis. Even after installation, the screens remain easily accessible for maintenance purposes. Video wall trolley 3x3

Display size: 55 inch Mounting: 3335 x 400 mm Max. weight: 44 kg/display Kit contains: • 2x PFT 8920, Video wall trolley undercarriage • 1x PFA 9129, Crossbar 1150 mm • 2x PUC 2920 Tube 2000 mm • 2x PFB 3419 Display interface bar • 4x PFS 3504 Display interface strips 3D

TVW2255 Video Wall Trolley 2x2

Specifications

Article number (SKU)	7922560
Colour	Black
EAN single box	8712285338564
Height	2178
Width	1915
Depth	1000
TÜV certified	Yes
Guarantee	5 years
Max. weight load (kg)	80
Max. horizontal hole pattern (mm)	1935
Max. screen size (inch)	55
Max. vertical hole pattern (mm)	400
Min. screen size (inch)	46

VOGEL'S HOLDING BV (©)

All rights reserved.
Subject to printing errors,
technical and price
amendments.

Date: 2022-06-02



Vogel's. For Sure.