

EB-PQ2010B



Perfect for anyone needing an ultra-high resolution experience, the EB-PQ2010B is the world's most compact 10,000lm 4K projector¹.

Designed to engage and captivate audiences with ultra-high resolution, large format content, the EB-PQ2010B uses 3LCD technology to deliver outstanding colour reproduction, while Epson's patented 4K Crystal Motion technology offers stunning image quality. Affordable and energy-efficient, the projector also features interchangeable lenses, a light and compact design and extensive connectivity.

The world's smallest and lightest 10,000lm 4K projector¹

Building on the success of the EB-PU Series, the EB-PQ2010B is not only the smallest and lightest in its class, but is highly affordable, versatile, energy-efficient and packed with advanced features.

A revolutionary 4K experience

Marvel at the clarity of the images produced by Epson's latest 4K technology. Combining its patented, state of the art 4K Crystal Motion and double micro-lens array technologies, Epson achieves a new benchmark in 4K image quality.

Fantastically flexible

Featuring a wide range of connectivity, including 12G SDI in/out and HDMI in/out supporting 120Hz 4K. This high brightness projector also benefits from cross-platform lens compatibility, using the same 4K lenses as the existing EB-PU Series, including the ELPLX02S zero-offset ultra-short throw lens which is perfect for immersive spaces. This projector is supplied 'body-only', allowing you to build the perfect solution for your installation.

Reliable

Built for exceptional reliability, the EB-PQ2010B is compatible with the ELPAF63 External Air Filter and provides up to 20,000 hours maintenance-free operation, or even longer in extended modes.

Extensive software

Compatible with the ELPEC01 camera, Epson Projector Professional Tool and Epson Config Tool for a wealth of calibration, assistance and control functionality.

DATASHEET / BROCHURE



KEY FEATURES

- **Patented 4K and imaging technology**
Outstanding 4K image quality delivers superb immersivity
- **Ultra-compact and lightweight**
The world's smallest and lightest 10,000lm 4K projector¹
- **Cross-platform lens compatibility**
Lets you build the optimal projection solution for every requirement
- **Fit-and-forget reliability**
Up to 20,000 hours maintenance free
- **Reduced environmental impact**
Energy-efficient with reduced requirements for packaging and transport

PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System	3LCD Technology, RGB liquid crystal shutter
LCD Panel	1.04 inch with C2 Fine

IMAGE

Color Light Output	10,000 Lumen- 7,000 Lumen (economy) In accordance with IDMS15.4
White Light Output	10,000 Lumen - 7,000 Lumen (economy) In accordance with ISO 21118:2020
Portrait Colour Light Output	10,000 lm
Portrait White Light Output	10,000 lm
Resolution	4K 3840 x 2160, 8.3m pixels, 16:9
Aspect Ratio	16:9
Contrast Ratio	Over 5,000,000 : 1
Native Contrast	3,000 : 1
Light source	Laser
Laser Light source	20,000 hours Durability High, 30,000 hours Durability Eco
Keystone Correction	Manual vertical: $\pm 45^{\circ}$, Manual horizontal $\pm 30^{\circ}$
Colour Video Processing	10 Bits
Colour Reproduction	Upto 1.07 billion colours
HDR support	HDR10, HLG

OPTICAL

Throw Ratio	0.34 - 7.16:1, Varies by lens
Zoom	Motorized, Varies by lens
Lens	Optical
Lens Shift	Varies by lens
Screen Size	Varies by lens
Projection Distance Wide	Varies by lens
Projection Distance Tele	Varies by lens
Projection Distance Wide/Tele	Varies by lens
Projection Lens F Number	Varies by lens
Projection Lens Focal Length	Varies by lens
Projection Lens Focus	Motorized
Offset	Varies by lens
Interchangeable Lens	Yes
Standard Lens	Not included

CONNECTIVITY

Interfaces	USB 2.0-A (2x), USB 2.0 Type B (Service Only), RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n (optional), HDMI in (2x), HDMI out, HDBaseT, Jack plug out, Near Field Communication (NFC), USB content playback, Remote, 12G SDI Input, 12G SDI Output
Network Protocol	HTTPS, IPv6, SNMP, ESC/VP.net, PJLink

ADVANCED FEATURES

Security	Kensington lock, Control panel lock, Padlock, Wireless LAN unit lock, Wireless LAN security, Password protection
Other features	21:9 aspect ratio support, A/V mute, Auto Power On, Auto source search, Direct Power on/off, Edge Blending, Frame interpolation, Freeze image, Horizontal and vertical keystone correction, Lens position memory, Long light source life, OSD copy function, Point correction, Quick Corner, Schedule Function, Web Control, Wireless LAN capable, iProjection App
Video Color Modes	Cinema, Dynamic, Natural, Presentation, DICOM SIM, Multi Projection, BT709
Projector control	via: Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery

EB-PQ2010B

WHAT'S IN THE BOX

- Cable cover
- Lens connector cap
- Main unit
- Power cable
- Remote control incl. batteries
- Information sheet
- Quick Start Guide
- Document Pack

PRODUCT SPECIFICATIONS

EB-PQ2010B

GENERAL

Power consumption	558 Watt (Normal On-Mode), 613 Watt (Normal Peak-mode), 483 Watt (Eco Peak-Mode), 0.5 Watt (Energy saving standby)
Heat Dissipation	2,084 BTU/hour (max)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Product dimensions	545 x 436 x 189 mm (Width x Depth x Height)
Product weight	18.8 kg
Noise Level	Normal:39 dB (A) - Economy:29 dB (A)
Supported Temperature	Storage -10° C - 60° C
Supported Humidity	Operation 20% - 80%, Storage 10% - 90%
	If the projector is suspended from a ceiling or wall mount and installed in an environment with heavy oil smoke or places where oils or chemicals are volatilized, places where a lot of smoke or bubbles are used for event staging, or where aroma oils are frequently burned, it can make certain parts of our products susceptible to a material degradation which over time could break and cause the projector to drop from the ceiling.
	If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional assistance.
Included Software	Epson Creative Projection, Epson Projector Config Tool, Epson Projector Content Manager, Epson Projector Management, Epson Projector Professional Tool
Options	Air filter, Camera module, Ceiling mount, Wireless LAN unit
Room Type / Application	Boardroom, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection Mapping, Rental / Staging, Signage / Retail, Visitor Attraction
Positioning	Ceiling Mounted, Desktop, Floor, Flying Frame, Table Mounted, Wall Mounted
Colour	Black

OTHER

Warranty	36 months Carry in Optional warranty extension available
----------	---

OPTIONAL ACCESSORIES

EB-PQ2010B

- Stacking Frame - ELPMB76 - EB-PU1000 Series
V12H006AN0
- Wireless LAN Adapter - ELPAP11 (2.4GHz & 5GHz)
V12H005A01
- Air Filter - ELPAF46
V13H134A46
- Camera Unit - ELPEC01
V12HA46010
- Ceiling Mount - ELPMB68
V12H006AE0
- External Air Filter - ELPAF63 - EB-PU1000 Series
V13H134AD0
- Portrait Adaptor - ELPMB78 - EB-PU Series
V12H006AQ0
- Rail Adaptor - ELPMB85 - EB-PU Series
V12H006AX0
- Tilt Adaptor - ELPMB81 - EB-PU Series
V12H006AT0

LOGISTICS INFORMATION

SKU	V11HB02880
EAN code	8715946719009
Country of Origin	China
Layer	2 Units

* Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com
Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04
(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742
Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway +47 67 11 37 00
Poland 0-0-800 4911299 (0,16 zł/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711) 465-9621
Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal – 0,99 kr/min, Lokala samtal – 0,30 kr/min, Utlandssamtal – 0,89 kr/min)
Switzerland 022 592 7923
Turkey (0212) 3360303 United Kingdom 0871 222 6702

1. As of January 2024. Main unit without lens.10,000lm in accordance with ISO 21118.
2. 4K (3840 x 2160) is the maximum physical resolution achieved using 4K Crystal Motion technology.
3. Energy efficient based on the power consumption data publicly available for comparable market leading products. Reductions in packaging and transportation requirements assumed based on physical product size and weight and/or packaging size and weight data available for comparable market leading products. As of February 2024.

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.
Product information is subject to change without prior notice.

